


DIN 931

Kuusioruuvi, osakierteinen
Hexagon screw, partial thread
Болт с шестигранной головкой (с неполной резьбой)
Kuusikantarpolt, osakeere

ISO 4014



	M5	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24	M27	M30	M36
b (L≤125)	16	18	22	26	30	34	38	42	46	50	54	60	66	78
b (125<L≤200)	22	24	28	32	36	40	44	48	52	56	60	66	72	84
b (L>200)	-	-	-	45	49	53	57	61	65	69	73	79	85	97
k	3,5	4	5,3	6,4	7,5	8,8	10	11,5	12,5	14	15	17	18,7	22,5
s	8	10	13	17	19	22	24	27	30	32	36	41	46	55

d	L (mm)	A4-70 1001	A4-80 10010	A2-70 7053	Zn 8.8 1053	HOT 8.8 5053	St 10.9 0052
M5	30		▲		▲		
	35		▲		▲		
	40		▲		▲		
	45		▲		▲		
	50		▲		▲		
	55		■		■		
	60		▲		▲		
	65					▲	
	70					▲	
	75						
M6	30		▲	▲	▲		
	35		▲	▲	▲		
	40		▲	▲	▲		
	45		▲	▲	▲		
	50		▲	▲	▲		
	55		■			▲	
	60		▲	▲	▲		
	65		▲	■	▲		
	70		▲	▲	▲		
	75					▲	
	80		▲			▲	
	90		▲			▲	
M8	30		▲				▲
	35		▲				▲
	40		▲	▲	▲	■	▲
	45		▲	▲	▲		
	50		▲	▲	▲	▲	
	55		▲	▲	▲		
	60		▲	▲	▲	▲	▲
	65		■	■	▲	▲	▲
	70		▲	▲	▲	▲	▲
	75		▲				▲
80			▲	▲	▲	▲	
90		▲	▲	▲	▲	▲	

d	L (mm)	A4-70 1001	A4-80 10010	A2-70 7053	Zn 8.8 1053	HOT 8.8 5053	St 10.9 0052
M8	100			▲	▲	▲	▲
	110				▲		
	120				▲		
	130				▲		
	140				▲		
	150				▲		
	160				▲		
	180				▲		
	200				▲		
	M10	35				▲	
40			▲	▲	▲	▲	
45			▲		▲	▲	
50			▲	▲	▲	▲	
55			▲			▲	▲
60			▲	▲	▲	▲	▲
65			■			▲	
70			▲	▲	▲	▲	▲
75			▲			▲	■
80			▲	▲	▲	▲	▲
90			▲	▲	▲	▲	▲
100			▲	▲	▲	▲	▲
110			▲	▲	▲	▲	■
120			▲	▲	▲	▲	▲
130			▲	■	▲	▲	▲
140			▲	■	▲	▲	■
M12	150		▲	▲	▲		
	160		▲	▲	▲	▲	
	180				▲	■	
	200			▲	▲		
	220				▲		
	240				■		
	260				■		
	40		▲				▲
	45		▲			▲	▲
	50		▲			▲	▲
55		▲			▲	▲	
60		▲			▲	▲	
65		▲			▲	▲	

© Ferrometal 08/2015